



TEREX DIESEL



DIESEL GENERATOR SET

TRX CU MC 2500



WATER



1-3 PHASE



50 Hz



STAGE2



DIESEL

Service		Standby	Prime
Power	kVA	2500	2250
Power	kW	2000	1800
Engine Speed	r.p.m	1500	
Voltage	V	230/400	
Power Factor	Cos Phi	0,8	

Standby power; In standby mode, the load value defined in the document describes annual usage under variable load conditions, averaging 70% load. Overloading is not permitted. Standby power is 10% more than prime power. It is used as backup power in areas where grid power infrastructure is available.

Prime power; This document specifies unlimited hours of use throughout the year with an average load factor of 70% of the power defined in the document during a 24-hour working period. It may be overloaded for a maximum of 1 hour at varying intervals during every 12-hour workday. This does not include continuous operation for 1 hour under overload conditions.

Continuous power; This allows for unlimited hours of use at the full (100%) of the defined power. Overloading beyond the defined power is not permitted. It is intended for use in locations without mains power.

QUALITY STANDARDS

Our generators comply with VDE 0530, BSE 4999 BS5000, IEC 34, EN12601; EN60204-1; TS ISO 8528-1 ... -13; EN12100-1; EN12100-2; EN61000-6-4; EN61000-6-2; EN61000-4-11; EN61000-4-6; EN61000-4-5; EN61000-4-2; EN55011; EN55016-2-1; EN55016-2-3; EN61000-3-2; EN61000-3-3; EN55014-1; EN61000-6-2; EN61000-4-3; EN61000-4-4; Manufactured in accordance with EN61000-4-8; EN61000-4-11; TS EN ISO 3744; TS EN ISO 3746; TS EN 60034-1; TS EN 60034-22; TS EN ISO 3046; BS 5514; NEMA MG 21; IEC 60034, BS 4999/5000, TS EN 60947-1..4 standards. ISO 9001-2015, ISO 14001-2015, ISO 45001-2018 and ISO 1002-2006 management system certificates have been obtained with accreditation from TUV AUSTRIA.

Our generators, with sound insulation enclosures up to 400 kW power, are manufactured in accordance with directive 2000/14/EC and are certified by SZUTEST.

Our generators are certified according to TS ISO 8528-4, TS ISO 8528-5, TS EN 13501-1+A1:2013 Insulation Foam Fire Behavior and TS EN ISO 9227 1500 Hour Neutral Salt Test. Our generators have CE Declaration.



TEREX DIESEL



www.terexdiesel.com.tr



Deri OSB. Mah.Tanen Sk. Deri OSB Sitesi NO:8 Tuzla-İSTANBUL



info@terexdiesel.com.tr



+90 850 532 63 20



+90 216 634 34 06



TEREX DIESEL



DIESEL GENERATOR SET

TRX CU MC 2500

ENGINE

Service	Features
Brand	CUMMINS
Model	QSK60G8
Engine Type	4 Stroke-Diesel
Injection Type	Direct Injection
Intake System	Turbo Charge & Aftercooler
Number of Cylinders	16
Cylinder Bore and Stroke	mm 159x190
Cylinder Volume	L 60,2
Cooling Type	Water Cooled
Fuel Consumption at Standby Load	l/h 437
Fuel Consumption at 100% Prime Load	l/h 394
Fuel Consumption at 75% Prime Load	l/h 291
Fuel Consumption at 50% Prime Load	l/h 200
Total Oil Capacity	L 280
Total Cooling Capacity	L 490
Governor Type	Type Electronic

The engine used in the generator set is a heavy-duty, industrial-type diesel engine. Depending on the model, the system is equipped with a water-cooled structure, naturally aspirated or turbocharged air intake system, mechanical or electronic governor, 12V/24V starter motor and charging alternator. The engine has replaceable air, fuel and oil filters, a flexible fuel hose, an oil drain valve and extension hose or oil drain pump. The system is also supplied with an industrial-type muffler, exhaust spiral or compensator, maintenance-free starter battery, and, in suitable models, an engine block water heater. Maintenance and operating manuals and electrical diagrams are provided with all products.

ALTERNATOR

Service	Features
Brand	MECC ALTE
Model	EC046-1.5L/4
Output Voltage	V 230/400
Frequency	HZ 50
Automatic Voltage Regulation	±% 1
Alternator Standby Power	kVA 2200
Alternator Continuous Power	kVA 2360
Power Factor	Cosφ 2200
Number of Cables	0,8
Winding Pitch	12
Protection Class	2/3
Warning System	IP23/H
AVR Model	P.M.G
Performance - PF 0.8 / 75% Load	% MX341B

The alternator used in the generator set is a brushless, single-bearing, 4-pole synchronous type with flexible disc connections. It has Class H insulation and IP21-IP23 protection class. The system is self-excited and provides voltage stability with an electronic voltage regulator (AVR). The alternator stator windings are designed with a 2/3 pitch to reduce harmonic distortions. All windings are protected with a special insulation varnish against oil, moisture and acidic effects, offering long-lasting and reliable operation.



TEREX
DIESEL

www.terexdiesel.com.tr

Deri OSB. Mah.Tanen Sk. Deri OSB Sitesi NO:8 Tuzla-İSTANBUL

info@terexdiesel.com.tr +90 850 532 63 20 +90 216 634 34 06



TEREX DIESEL



DIESEL GENERATOR SET

TRX CU MC 2500

DIMENSIONS

OPEN TYPE



LxWxH	mm	5150x2500x3200
Weight	kg	12850
Fuel Tank	lt	2350

CANOPIED



LxWxH	mm	6000x2500x3900
Weight	kg	14100
Fuel Tank	lt	2350

CABIN FEATURES

- Modular design, sound insulation cabin
- Cabin assembly performed with bolts and nuts without welding
- Cabin parts painted with epoxy polyester exterior powder paint using nanotechnology
- IP23 protection class
- Design suitable for easy generator maintenance
- Lockable doors on both sides
- Emergency stop button in a special, non-protruding recess on the cabin's exterior surface
- Transparent panel window
- Fireproof acoustic foam insulation
- Nanotechnology cleaning system
- Container optional

GENERATOR PROTECTION AND ALARMS

- High engine temperature
- Low oil pressure
- Excessive and low engine speed
- Low radiator water level
- Excessive current
- Excessive and low generator voltage and frequency
- Start/stop malfunction

SILENCER OPTIONS

- Industrial type
- Critical type Silencer
- Hospital type

CABIN OPTIONS

- Standard Cabin
- Quiet Cabin
- Special Type Cabin

OPTIONAL EQUIPMENT

- Charging ammeter
- Thermal magnetic circuit breaker (in automatic models)
- Hospital/Critical type muffler
- Sound insulation cabinet designed according to modular principle
- Trailer
- Synchronization panel for 2-16 generators
- 3-pole/4-pole power transfer panel
- Fuel heater, oil heater
- Alternator heater
- Automatic fuel filling system
- Fuel water separator filter
- PMG warning system



TEREX
DIESEL

www.terexdiesel.com.tr



Deri OSB. Mah.Tanen Sk. Deri OSB Sitesi NO:8 Tuzla-İSTANBUL



info@terexdiesel.com.tr



+90 850 532 63 20



+90 216 634 34 06



TEREX DIESEL



DIESEL GENERATOR SET

TRX CU MC 2500

OPTIONAL GENERATOR CONTROL DEVICES

Next-generation single generator control units combining multifunctionality for backup and main power applications and extensive communication with EFI engines.

Datakom DKG 309



Datakom D500



Datakom D500-GSM



EMKO Trans-AUTO



DEEPSEA 7320



ComAp AMF25



	Datakom DKG 309	Datakom D500	Datakom D500-GSM	Deepsea 6120	Deepsea 7320	ComAp AMF25	EMKO Trans-AUTO
Automatic Master Monitoring	✓	✓	✓	✓	✓	✓	✓
Manual Operation	✓	✓	✓	✓	✓	✓	✓
Remote Operation	OPTIONAL	OPTIONAL	✓	X	OPTIONAL	OPTIONAL	OPTIONAL
Remote Monitoring with SIM Card	X	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL
Optional Options (Horn, Oil-Fuel, etc.)	✓	✓	✓	✓	✓	✓	✓
Warning Light and MIM Diagram	✓	✓	✓	✓	✓	✓	✓
Battery Charger	✓	✓	✓	✓	✓	✓	✓
RS-485 Communication	OPTIONAL	✓	✓	X	✓	OPTIONAL	✓
Ethernet (TCP-IP) Communication	X	✓	✓	X	OPTIONAL	OPTIONAL	OPTIONAL

GENERATOR CONTROL DEVICES FOR SYNCHRONIZATION SYSTEMS

The new generation synchronized generator control unit has all kinds of communication and functionality.

Datakom D500 MK2



Datakom D700



DEEPSEA 8610




DEEPSEA 8620



DEEPSEA 8660



ComAp IntelliCompact NT SPtM



ComAp IntelliGen BaseBox



ComAp IntelliGen 200



TEREX DIESEL

www.terexdiesel.com.tr



Deri OSB. Mah.Tanen Sk. Deri OSB Sitesi NO:8 Tuzla-İSTANBUL



info@terexdiesel.com.tr



+90 850 532 63 20



+90 216 634 34 06